

BLU GLASS SYSTEM

Our Blu Glass system caters for your high volume needs, dispensing chilled still and sparkling water at the touch of a button.

- Pure Chilled Still & Sparkling Water
- Push Button Autofill
- Portion Controlled (2 settings)
- Labour Saving
- Continuous Supply 60+ Litres
- Filters down to 0.5 micron
- UV sanitisation

Technical Details

Filterboard	H770mm x W460mm x D120mm	UV 0.035amps/8 watts
Blu Glass tap	H510mm x W190mm x D220mm	Requires 50mm hole
Combi cooler	H550mm x W460mm x D460mm	3.8amps / 874 watts
Food grade CO2	H700mm x W180mm	Client to supply (BOC)




INSTALLATION REQUIREMENTS

- Electrician to install:
 1 x 13amp IP66 socket at HIGH level (for UV connection on filterboard)
 - 2 x 13amp IP66 sockets at LOW level (for combi cooler and Blu Glass tap)
- Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at HIGH level
 1x Mains drain point (optional)
- Order from BOC gas:2 x SB sized food grade CO2 bottles

BLU BAR

Our compact counter top Blu Bar is perfect for medium volumes of chilled still and sparkling water. The countertop design means that its perfect for venues with minimal space.

- Pure Chilled Still & Sparkling Water
- Space saving, countertop
- Continuous supply 45 litres
- Filters down to 0.5 micron
- UV sanitisation





Filterboard	H770mm x W460mm x D120mm	UV 0.035amps/8 watts
Blu Bar counter top unit	H566mm x W360mm x D565mm	2.3amps / 529 watts
Food grade CO2	H700mm x W180mm	Client to supply (BOC)



- Electrician to install:
 1 x 13amp IP66 socket at HIGH level (for UV connection on filterboard)
 - 1 x 13 amp IP66 sockets at LOW level (for the Blu Bar unit)
- Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at HIGH level
 1x Mains drain point (optional)
- Order from BOC gas:2 x SB sized food grade CO2 bottles

BLU FLAVOUR

Our Blu Flavour is perfect for guest self-serve in lobbies, conference areas and gyms/spas, providing still and sparkling flavoured water.

- Three syrup flavours with the choice of pure still or sparkling water
- EcoPure Waters supplies own range of natural, healthy flavours
- Space saving countertop unit
- Filters down to 0.5 micron
- UV sanitisation

Technical Details

Filterboard	H770mm x W460mm x D120mm	UV 0.035amps/8 watts
Blu Flavour counter top unit	H547mm x W344mm x D516mm	1.9amps / 390 watts
Syrups per box	H200mm X W285mm X D220mm	
Food grade CO2	H700mm x W180mm	Client to supply (BOC)



- Electrician to install:
 2 x 13amp IP66 sockets at LOW level (for UV and system)
- Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at LOW level
 - 1 x Mains drain point (optional)
- Order from BOC gas:1 x SB sized food grade CO2 bottle

BLU SODA

Our Blu Soda system is perfect for small offices or break out areas. The stylish design means it looks great front of house.

- Pure Chilled Still & Sparkling Water
- Space saving
- Push button dispense
- Continuous supply 10 litres
- Filters down to 0.5 micron
- UV sanitisation
- Perfect for our shorter bottles or a glass
- Dispense straight to glass
- Optional free-standing unit

Technical Details

Filterboards	H770mm x W460mm x D120m	UV 0.035amps/8 watts
Blu Soda counter top unit	H420mm x W260mm x D500mm	1amp / 230 watts
Food Grade CO2	H700mm x W180mm	Client to supply (BOC)



 Electrician to install:
 1 x 13amp IP66 socket at HIGH level (for UV connection on filterboard)

1 x 13 amp IP66 sockets at LOW level (for Blu Soda unit)

 Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at HIGH level

1 x Mains drain point (optional)

Order from BOC gas:2 x SB sized food grade CO2 bottles

QUATTRO FILLER

4 BOTTLE GRAVITY FED BOTTLING SYSTEM

Our Quattro system is the fastest way to fill large quantities of ambient still water, ideal for large hotels.

- Pure Still Ambient Water
- Ideal Stadia / Housekeeping Solution
- Fills 4 bottles in 30 secs
- Recommended for 400+ bottles a day
- Filtered down to 0.5 micron
- UV sanitisation

Technical Details

2x filterboards	H770mm x W460mm x D120m	UV 0.035amps/8 watts
Quattro unit	H1600mm x W600mm x D500mm	
Food Grade CO2 Gas	H700mm x W180mm	Client to supply (BOC)



INSTALLATION REQUIREMENTS

- Electrician to install:
 2 x 13amp IP66 socket at HIGH level (for 2 UV units on filter board)
- Plumber to install:
 2 x 15mm BSP isolator valve connection to cold non softened mains located at HIGH level
- Plumber / Client to install:
 Waste connection within 1 metre of location BASE Level
- Minimum width of working table surface required 1200mm

STILL AMBIENT FSU

Our ambient free standing unit is perfect for guests to help themselves. Its minimalist design is perfect for any location.

- Pure Ambient still water
- Compact free standing design
- Continuous supply of water
- Filters down to 0.5 micron
- UV sanitisation

Technical Details

Filterboard	H770mm x W460mm x D120mm	UV 0.035amps/8 watts
Single font tap	Physical Height: H640mm x W50mm Dispense Height: 390mm	
Tower	H959mm x W491mm x D554mm	



- Electrician to install:
 1 x 13amp IP66 socket at Low level (for UV connection on filterboard)
- Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at Low level
 1x Mains drain point (optional)

DOUBLE FONT

Our Double Font system is a stylish front of house system for dispensing high volumes of chilled, still and sparkling water.

- Pure chilled, still and sparkling water
- Compact, space-saving design
- High volume dispense
- Continuous supply of 60 80+ litres
- Filters own to 0.5 micron
- UV sanitisation

Technical Details

Filterboard	H770mm x W460mm x D120mm	UV 0.035amps/8 watts
Double font tap	Physical Height: H640mm x W220mm Dispense Height: 390mm	Requires a 35mm hole
Combi cooler	H550mm x W460mm x D460mm	3.8amps / 874 watts



- Electrician to install:
 1 x 13amp IP66 socket at HIGH level (for UV connection on filterboard)
 - 1 x 13 amp IP66 sockets at LOW level (for Combi Cooler)
- Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at HIGH level
- Order from BOC gas:2 x SB sized food grade CO2 bottles

SINGLE FONT

Our Single Font system is a stylish front of house system for dispensing high volumes of chilled, still water.

- Pure chilled, still water
- Compact, space-saving design
- High volume dispense
- Continuous supply of 60 80+ litres
- Filters own to 0.5 micron
- UV sanitisation

Technical Details

Filterboard	H770mm x W460mm	UV 0.035amps/8
	x D120mm	watts
Single font tap	Physical Height: H640mm x W50mm Dispense Height: 390mm	Requires a 35mm hole
Cooler	H280mm x W490mm x D450mm	2amps / 460 watts
Food Grade CO2	H700mm x W180mm	Client to supply (BOC)



INSTALLATION REQUIREMENTS

- Electrician to install:
 1 x 13amp IP66 socket at HIGH level
 (for UV connection on filterboard)
 - 1 x 13amp IP66 sockets at LOW level (for Cooler)
- Plumber to install:
 1 x 15mm BSP isolator valve connection to cold no softened mains located at HIGH level

CAPPING MACHINE

Our Capping machine is the ideal solution for a plastic free tamper evident finish to your bottle.

- Caps 400-600 bottles per hour
- Easy to operate
- Robust and hard wearing
- Gives an elegant, tamper proof finish

Technical Details

Capping machine

H992mm x W400mm Weight: 100kg



INSTALLATION REQUIREMENTS

Electrician to install: 1 x 13amp IP66 socket at Work top height

